



COLOUR DOME CAMERA

ADV 28F



SPECIFICATION

Model	ADV 28F	
Image Sensor	1/3" Sony Color CCD Sensor	
Scanning System	2:1 Interlace	
	30 Frames (NTSC)	25 Frames (PAL)
Effective Pixels	525 Lines Interlaced (NTSC)	625 Lines Interlaced (PAL)
	510 (H) x 492 (V) (NTSC)	500 (H) x 582 (V) (PAL)
Resolution	420 TV Lines	
Minimum Illumination	0.5 Lux / F 2.0	
S/N Ratio	More Than 48dB (AGC Off)	
Video Output	1.0 Vp-p composite, 75ohm	
Gamma Ratio	0.45	
White Balance	Auto	
Back Light Compensation	Auto	
Auto Gain Control	Auto	
Iris Mode	AES	
Synchronization	Internal	
Electronic Shutter	1/60 to 1/100,000 sec (NTSC)	1/50 to 1/100,000 sec (PAL)
Lens	f = 3.6mm / F2.0	
Power Source	DC12V ± 10%	
Power Consumption	200mA	
Operating Temperature	- 20°C to + 50°C	
Weight / Dimension	Approx. 130g / Ø 98.0 x 65.0H mm	

Design and specifications are subject to change without prior notice

