



OS-214TT

OS-214TT

The OS-214TT offers value and performance in a printer that has both thermal transfer and direct thermal printing capabilities. Standard features and adaptable options are available to meet a wide range of medium volume printing applications. The OS-214TT prints a large variety of labels for applications ranging from office shipping to general tags and labels. A small footprint allows use in areas with a minimum of space, while its light weight makes it easy to place in new locations. The OS-214TT provides exceptional value and flexible performance in a space-saving design.



OS-314TT

OS-314TT

The OS-314TT is an affordable, high-performance thermal transfer / direct thermal printer offering laser quality 300 dpi print resolution for high-density images. A 32-bit microprocessor and 2 MB of built-in memory delivers fast throughput for label printouts of up to 14 inches. Standard features and flexible options offer a versatile, powerful printer that will continue to provide exceptional operational value over time. The OS-314TT provides a winning combination of the latest technology and maximum performance in a cost-effective, space-saving package.



Specifications	OS-214TT	OS-314TT
Printing Method	Thermal Transfer	Thermal Transfer
Printing Resolution	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
Printing Speed	2 ~ 3 ips (51 ~ 76 mm/s)	2 ips (51 mm/s)
Printing Length	Max 8" (203 mm)	Max 14" (355 mm)
Printing Width	Max 4.1" (104mm)	Max 4.1" (104mm)
Memory	512KB DRAM 512KB Flash ROM	2MB DRAM 512KB Flash ROM
CPU Type	16 bit RISC microprocessor	32 bit RISC microprocessor
Media Sensor	Reflective	Reflective
Display	LED indicator x 2	LED indicator x 2
Operation Interface	Button x 1	Button x 1
Communication Interface	Centronics parallel RS-232 serial	Centronics parallel RS-232 serial
Fonts	Int'l character sets standard 5 alpha-numeric fonts from 0.049" ~ 0.23" H (1.25mm ~ 6.0mm) All fonts are expandable up to 24 x 24 4 direction 0° ~ 270° rotation Soft fonts are downloadable	
Barcodes	Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128 (Subset A, B, C) Codabar, Interleave 2 of 5, EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25, Maxicode, PDF-417, Data Matrix	
Graphics	PPLA:PCX, BMP, IMG, HEX, GDI PPLB:PCX, Binary raster, GDI	
Software	Argox PPLA/PPLB Language Windows Driver (Win 98/2000/NT/XP) Label editing software - BarTender / Printer Utility	
Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper Max width 4.3" (108mm) Min width 1.0" (25.4mm) Thickness 0.0025" ~ 0.01" (0.0635mm ~ 0.254mm) Max roll capacity 4.3" (109mm) OD Core size 1" (25mm) ID	
Ribbon	Wax, Wax/Resin, Resin (Outside coating ribbon) Ribbon width - 2", 4" Ribbon roll - max OD 1.45" (37mm) Ribbon length - max 91 m Core size - ID 0.5" core (13mm) with notch	
Mechanism Request	Fan fold paper back cover, face-out ribbon run way, face-out media run way, un-adjustable TPH carrier	
Dimensions	W186 x H153 x L278 mm, 4.2lbs (1.9kgs)	
Power Source	110/220 VA ± 10%, 50/60Hz	
Agency Listing	CE, UL, CUL, FCC Class A, CCC	
Operation Environment	40° F ~ 100° F (4° C ~ 38° C) ; 10 ~ 90% non-condensing	
Optional Items	Cutter, Dispenser kit, Real time clock card, ArgoKee, 2MB Asian Font card (Traditional Chinese, Simplified Chinese, Korean and Japanese)	

Specifications subject to change without notice

